

## NOTICE TO BIDDERS

Sealed bids will be received until 2:00 p.m. on August 22, 2019 and then publicly opened and read at 345 S. Main, Bolivar City Hall, Polk County, Missouri, for a new Truck Mounted Vacuum or Regenerative Air Street Sweeper for the Street Department.

The Street Sweeper specifications and Bid Documents are on file and may be examined and obtained between the hours of 8:00 a.m. & 5:00 p.m. Monday thru Friday at the Offices of the Public Works Director or City Clerk, at Bolivar City Hall, PO Box 9, Bolivar, MO 65613, 417-326-2489, or on the city web site at [www.bolivar.mo.us](http://www.bolivar.mo.us).

---

Paula Henderson,  
City Clerk

## **Bolivar Public Works – Street Department**

The following are minimum specification standards;

### **Truck Mounted Vacuum or Regenerative Air Street Sweeper**

A new truck chassis and a mounted vacuum or regenerative air street sweeper unit. Truck must have a minimum 250 h.p. diesel engine with a automatic transmission . chassis must have a minimum 32,000 pound GVWR and meets all current emissions and motor vehical standards . Controls for all drive and sweeping functions shall be in the cab. Dual operating controls RH and LH ,RH and LH grab handles, seatbelts, RH and LH heated and electric mirrors with 8 inch spot mirrors. Truck must have ac, heat and defroster . Intermittent windshield wipers and washer . High back air suspension bucket seats for both operator positions . AM FM radio . Engine protection system utilizing coolant temperature,oil pressure, ect. Standard seal multiple beam headlights. Air breaks cam type breaks.

Hopper must be 7 Cubic yards or greater and must be made from stainless steel material.

Auxiliary hose and wand. High pressure /high volume pump with hand lance and self-retracting hose reel .

LED Strobes warning lights and backup alarm

If the unit is Regenerative, unit MUST have a wash system for the head.

Unit must have dust control – spray bars and gutter broom nozzles . A inside cad low water indicator light. No less then a 220 gal. water tank {industrial grade polyethylene or stainless steel tank}

A hydrant fill hose require and a air gap between the tank hydrant hose connector.

Tilt gutter brooms located on each side of the cab .

Camera System Left & Right hand – rearview camera.

Sweeper engine - minimum 4 cylinder turbo charged diesel ; engine should have temperature and oil and coolant level shut-off and emergency shut-off.